




## DRUM FILTER serie 80 with tank



Filter 4-80 with stainless steel tank and cover.



Maintenance free



### DRUM FILTER Serie 80 with Stainless steel tank

Hydraulic flow filtered limited to 40 l/s (144 m<sup>3</sup>/h).

It can be quickly installed in cramped places due to its low size and weight.

It is suitable for closed circuits, laboratories, testing station etc...

The drum is supplied with 2,4, 6 or 8 filter plates. It operates at 5 rpm.

### Strong points :

- ✓ Filtration plates frames made of stainless steel.
- ✓ An optimized water saving rinsing system.
- ✓ Entirely made of AISI 304L or AISI 316L stainless steel.
- ✓ Designed to be simple, robust and reliable.
- ✓ Free maintenance system. No chain, but a drive belt.



☆ STAINLESS STEEL MESH ☆  
HIGH QUALITY



*Drum driven by belt, simple and economical.*



**Table giving water volumes handled (l/s) :**

Filter model :		2-80	4-80	6-80
Water with maxi <b>10 mg/l</b> of waste <b>Outlet fish farm</b>	Filter plates mesh			
	26µ	13	26	39
	36µ	23	46	50
	40µ	26	50	50
	63µ	34	50	50
	80µ	38	40	40
	100µ	40	40	40
D R U M F I L T E R W I T H T A N K				
Water with maxi <b>25 mg/l</b> of waste <b>Recirculation system.</b>	36µ	13	26	39
	40µ	18	36	40
	63µ	25	40	40
	80µ	32	40	40
<i>In case of waste over 25 mg/l , please consult us.</i>				
Motor power 3x400v (w)		250	250	250
Rinsing (l/s) at 3 bars with 80µ		0,13	0,20	0,40
Filter surface (m2)		0,86	1,72	2,58
Number of plates		2	4	6

*Ø250 in standard/Ø315 on request*



*A filter 4-80 installed on a recirculation system.*

*Pictures and technical data are not contractual. FAIVRE Sarl can bring any modification to its equipment at any time.*