



### Technical Characteristics

- Patented high speed motor (VFD integrated)
- Compact & light weight
- MODBUS compatible
- 18,000 hours maintenance free

### Electric Motor


- Insulation Class H
- VFD/VSD integrated
- Adjust speed instantly via HMI or MODBUS 3rd party PLC
- IP65

### Options

- Single or 3Ph power
- 50 or 60Hz

		Pressure																	
Rpm	15kPa		16kPa		20kPa		25kPa		30kPa		35kPa		40kPa		45kPa		50kPa		
	Flow Rate (m <sup>3</sup> /min)	Power (kW)	Flow Rate (m <sup>3</sup> /min)	Power (kW)	Flow Rate (m <sup>3</sup> /min)	Power (kW)	Flow Rate (m <sup>3</sup> /min)	Power (kW)	Flow Rate (m <sup>3</sup> /min)	Power (kW)	Flow Rate (m <sup>3</sup> /min)	Power (kW)	Flow Rate (m <sup>3</sup> /min)	Power (kW)	Flow Rate (m <sup>3</sup> /min)	Power (kW)	Flow Rate (m <sup>3</sup> /min)	Power (kW)	
60k	4.00	1.37	3.65	1.78	2.90	1.33	1.90	1.03											
65k	4.50	2.04	4.10	2.00	3.65	1.92	3.10	1.80											
70k			4.40	2.44	4.30	2.42	3.75	2.31	3.13	2.11	1.95	1.53							
75k			4.80	3.00	5.00	3.00	4.25	2.89	3.85	2.78	3.48	2.69	2.38	2.11					
80k					4.90	3.58	4.75	3.53	4.50	3.54	4.10	3.33	3.63	3.13	2.75	2.67	1.875	2.06	

### Performance Range



Get Smart About Energy –  
Scan for Your Savings.

for more information visit  
[www.sprintex.com.au](http://www.sprintex.com.au)  
[www.smartaeration.au](http://www.smartaeration.au)

